



Electric water heaters



- Enamelled steel water tank
- Temperature regulation with external knob
- **New ohmic protection system (reduced consumption of the magnesium anode)**
- Polyurethane insulation without CFC and HCFC
- Analogic thermometer (excluding 10-15 litres models)
- Built-in dielectric fitting
- Light indicator
- Grade of protection: IP24

	Product code	Class	Capacity l	Installation	Rating/Voltage W/V	Load profile	Dimensions	Net weight kg
V530	7110906	C	30	Upright	1.200/230	S	623 x 338 mm	10,3
V550	7110907	C	50	Upright	1.200/230	M	610 x 433 mm	16,5
V580	7110908	C	80	Upright	1.200/230	L	854 x 433 mm	21,5
V510	7110909	C	100	Upright	1.200/230	L	1018 x 433 mm	25
O580	7110910	C	80	Horizontal	1.500/230	M	854 x 433 mm	19,8
O510	7110911	C	100	Horizontal	1.500/230	L	1018 x 433 mm	21,4
V580 TD	7110912	C	80	Thermoelectric upright (right connection)	1.500/230	L	854 x 433 mm	24,8
V580 TS	7110913	C	80	Thermoelectric upright (left connection)	1.500/230	L	854 x 433 mm	24,8
V510 TD	7110914	C	100	Thermoelectric upright (right connection)	1.500/230	L	1018 x 433 mm	29,5
V510 TS	7110915	C	100	Thermoelectric upright (left connection)	1.500/230	L	1018 x 433 mm	29,5
R501	7110903	B	10	Above sink	1.200/230	XXS	456 x 255 mm	6
R501 SL	7110902	B	10	Under sink	1.200/230	XXS	456 x 255 mm	6
R515	7110905	B	15	Above sink	1.200/230	XXS	399 x 338 mm	7,4
R515 SL	7110904	C	15	Under sink	1.200/230	XXS	399 x 338 mm	7,4